

LYNX

DESCRIPTION

LYNX provides a low-noise alternative to standard grit blast nozzles. The technology is field proven and provides the necessary productivity and durability with the improved HSE footprint.

FEATURES

- < 99 dB* noise level
- Achieved 11 dB noise reduction
- TC insert for prolonged durability
- Optimized grip
- Recognizable colour

NOZZLE SIZES

LYNX nozzle sizes available
#5, #6, #7, #8, #10, #12



LYNX TECHNICAL DATA

Size	#5 (⁵ / ₁₆ " , 8mm)
Weight	1850 g
Length	280 mm
Diameter	55 mm
Connection	50mm Contractor
Entry diam.	1 1/4" , 31,8mm
Liner	Tungsten Carbide
Liner Style	Venturi
Damper alloy	Tungsten Carbide
Jacket/Grip	TPU 85° Shore
Rec. air supply	3840 L/ _{min} , 7 Bar
Rec. blast hose ID	1" - 1 1/2"

LYNX BLAST OPERATOR NOISE LEVEL*

Hose pressure	LpA [dB]
7,0 bar / 102 psi	98,6
6,5 bar / 94 psi	98,5
6,0 bar / 87 psi	97,6
5,5 bar / 80 psi	97,2
5,0 bar / 73 psi	96,5
4,5 bar / 65 psi	96,2
4,0 bar / 58 psi	95,1

*Based on measured nozzle #5 done by "Brekke & Strand Akustikk", report AKU-01-11005900